

12/12/01




12-17-01

A

EXPRESS MAIL CERTIFICATE

DATE 12/12/01 LABEL NO. EK146996369US

I HEREBY CERTIFY THAT ON THE DATE INDICATED ABOVE I DEPOSITED THIS PAPER OR FEE WITH THE U.S. POSTAL SERVICE AND THAT IT WAS ADDRESSED FOR DELIVERY TO THE U.S. PATENT & TRADEMARK OFFICE, PO BOX 2327, ARLINGTON, VA, 22202 BY "EXPRESS MAIL POST OFFICE TO ADDRESSEE" SERVICE.



TITLE: Portable Wind-Powered Light

INVENTOR: Daniel Toulon

DOC NO.: 12135

BACKGROUND OF THE INVENTION

The invention relates to a portable wind powered light that can be attached to a moving object or the like to allow generated wind to illuminate a light source.

People who are driving their bicycles or working in their gardens often require the assistance of a light source to aid them in their endeavour. Because these activities are participated in outdoors, the lack of a reliable power source is typically a problem. Most of these light sources utilize batteries as a power source. Often, however, batteries have proven to be unreliable,

alternate power source is necessary to power these light sources.

The present invention attempts to solve the abovementioned problem by providing a portable light source that uses a wind-powered generator to provide a power to a light source.

Several references show various light sources that are portable for use in a plurality of locations and for a plurality of uses.

While these units may be suitable for the particular purpose employed, or for general use, they would not be as suitable for the purposes of the present invention as disclosed hereafter.

SUMMARY OF THE INVENTION

It is an object of the invention to produce a portable
wind powered light that can be attached to a moving object
or the like to allow generated wind to illuminate a light
source including a generator disposed interiorly of a
protective cylindrical housing. The housing has a first
end, a second end, and a cylindrical side wall therebetween.
A propeller is coupled with the first end of the cylindrical
housing. The propeller is operably coupled with the
generator. The propeller includes a plurality of vanes
extending outwardly from a rotatable main member. A support
arm extends outwardly from the second end of the cylindrical
housing. The support arm includes an inner portion in a co-
linear relationship with the cylindrical housing. The
support arm includes an outer portion extending angularly
from the inner portion. A light source is coupled with the
outer portion of the support arm. The light source is in
communication with the generator. A clip member is adapted
for coupling with a tubular object. The clip member has an
extension arm extending upwardly therefrom. The extension
arm has a free upper end secured to the cylindrical side
wall of the cylindrical housing.

To the accomplishment of the above and related objects

the invention may be embodied in the form illustrated in the accompanying drawings. Attention is called to the fact, however, that the drawings are illustrative only. Variations are contemplated as being part of the invention, limited only by the scope of the claims.

5

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings, like elements are depicted by like reference numerals. The drawings are briefly described as follows.

FIG 1 is a perspective view of the present invention.

FIG 2 is a cross-sectional side view of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

It will be noted in the various figures that the device relates to a portable wind powered light that can be attached to a moving object or the like to allow generated wind to illuminate a light source. In its broadest context, the device consists of a generator, a propeller, a support arm, a light source, and a clip member. Such components are individually configured and correlated with respect to each other so as to attain the desired objective.

The generator 12 is disposed interiorly of a protective cylindrical housing 14. The housing 14 has a first end 16, a second end 18, and a cylindrical side wall 20 therebetween.

The propeller 22 is coupled with the first end 16 of the cylindrical housing 14. The propeller 22 is operably coupled with the generator 12. The propeller 22 includes a plurality of vanes 24 extending outwardly from a rotatable main member 26.

The support arm 28 extends outwardly from the second end 18 of the cylindrical housing 14. The support arm 28 includes an inner portion 30 in a co-linear relationship with the cylindrical housing 14. The support arm 28 includes an outer portion 32 extending angularly from the

inner portion 30.

The light source 34 is coupled with the outer portion 32 of the support arm 28. The light source 34 is in communication with the generator 12. Thus, when the propeller 22 is rotating sufficiently, the generator 12 will be activated to cause the light source 34 to be illuminated.

The clip member 36 is adapted for coupling with a tubular object. In the preferred embodiment, the clip member 36 will allow the present invention to be secured to a handle bar area of a bicycle. The clip member 36 has an extension arm 38 extending upwardly therefrom. The extension arm 38 has a free upper end secured to the cylindrical side wall 20 of the cylindrical housing 14.